PhaseWeave

Graph reasoning and cyclic qudits for historical market replay

Research methods and experimental results
20 November 2026

Abstract

We forecast two directed FX triangle margins one second ahead. A paired width-200 experiment adds currency, pair and overnight funding references to quotes, trades and document context on the same historical windows. October mean absolute error falls from 0.156397 to 0.155883 log basis points. A paired UTC-day interval favors the reference model in October and includes zero on September stress and unseen CHF triangles. We report the evidence clocks, verify a corrected genus-one cellular example and distinguish model error from the availability of cross-market data.

1 Graph and observation model

At decision time t, let $G_t = (V, E_t)$ be a directed attributed graph. A vertex is a currency or spot asset. An edge records its source, side, timestamp, rate, and when available the displayed quantity and unit. At most the last observed quote with timestamp at or before t is used. For pair A/B with bid b and ask a,

$$w_{AB} = \log b, \qquad w_{BA} = -\log a.$$

A path $P = (v_0, \dots, v_k)$ with per-leg log fees $f_i \geq 0$ has margin $10^4 \sum_{i=1}^{k} (w_{v_{i-1}v_i} - f_i)$ in log basis points. The verifier treats a path with a stale or absent edge as unavailable.

Proposition 1 (Change of units)**.** *For a closed path, replacing every directed log rate by $w'_{uv} = w_{uv} + h(v) - h(u)$ preserves its margin, with unchanged log fees.*

Proof. The additional terms telescope to $h(v_k) - h(v_0) = 0$. □

Bid and inverse ask are separate directed rates. Their sum is $\log(b/a)$, while a mid-price connection can be antisymmetrized for curvature analysis. The observable log margin retains its sign and magnitude even when a compact phase representation wraps. Fenn et al. analyze the distinction between positive quote products and execution of all legs. [2]

2 Surface incidence and cyclic features

Follow the clean-dessin construction in the GRH research atlas. [1] Let α reverse darts and let σ rotate darts around their tails. Require a fixed-point-free involution, a valid permutation, and transitivity. The permutation $\phi = \alpha\sigma^{-1}$ traverses the inverse oriented face boundaries in this convention. The genus of the corresponding connected oriented surface is determined by

$$2 - 2g = c(\sigma) - \frac{|H|}{2} + c(\phi),$$

where H is the dart set and c counts permutation cycles. Market graph connectivity does not choose a rotation system. The rotation rule must be explicit, and orientation and genus controls test for dependence on that choice.

A six-dart torus illustrates why the oriented attaching word matters. After subdividing its three parallel edges, the counts become $(V, E, F) = (5, 6, 1)$. With all six new edges oriented from black to white, set $p = (1, -4)$, $q = (2, -5)$ and $r = (3, -6)$. Each pair travels between the same two black vertices through a different white vertex. The face $pr^{-1}qp^{-1}rq^{-1}$ closes in twelve steps, uses each edge once each way, and leaves pq^{-1}, pr^{-1} as an integral

basis of H_1. The six-letter word printed in the historical subdivision has nonzero boundary $3(v_{\text{black},2} - v_{\text{black},1})$. [7]

The ToricGT decrement convention for a q-level state is $Ce_j = \omega^j e_j$, $Se_j = e_{j-1 \bmod q}$, with $\omega = e^{2\pi i/q}$. Direct action on e_j gives $SC = \omega CS$ and $C^q = S^q = I$. The historical surface-order companion shift uses the increment direction and a formal uniformizer at the wrap. The unitary circuit uses a unit-modulus complex wrap. Use interference or Hermitian components of a Weyl expectation to observe relative phases.

3 Graph models and ablations

Compare GCN, GAT, typed MPNN and a Node/Edge TokenGT backbone with matched data and compute. [3] The shared graph schema also represents the ConvexTok byte DAG, the prediction trace and typed evidence. A conditioned discrete-flow head proposes valid graph edits or ordered cycles. A basis operator head reconstructs the time-varying margin field. Tropical attention and cyclic-qudit features are varied independently. Compare the circuit against trigonometric, frozen, unentangled and phase-scrambled features.

The completed pilot included 24 width-200 proxies, two wider transfers and 12 matched circuit and attention controls. Validation selected a separate checkpoint for each width in subsequent full-epoch training. The quote-only width-200 model reached October MAE 0.155829 under its own schedule. We use separately matched arms below to estimate the effect of adding reference inputs. [6, 8]

4 Measured feasibility

On the verified RTX 4090 host, the HistData pilot validated 22,819,287 quote rows from nine files. The sources were EUR/USD, USD/JPY and EUR/JPY in August through October 2026. Tied timestamps use the minimum bid and maximum ask. The pilot used a 250 ms maximum age, a one-second forecast horizon, and 0.1 log-bps extra fee per leg.

Month	Future samples	Positive margins	Persistence MAE (bps)
August	148,646	2	0.1992
September	247,696	18,878	0.2192
October	241,314	4	0.1999

September 17 and 18 account for 17,511 positive labels. Every source volume was zero. These facts motivate session-level uncertainty and checking the positive-margin regime with an independent feed. Three Gate spot depth logs provide a follow-on reconstruction dataset with 1,940,033 rows. These measurements are feasibility diagnostics.

Explicit statevector simulations used batches of four 16-qubit states, eight eight-qutrit states and eight six-ququint states at four layers each. The maximum state norm error on the GPU was 6.20×10^{-6}. The CPU–CUDA differences were at most 1.06×10^{-6} for the mean observable and 2.90×10^{-6} for the tested derivative. The largest difference between automatic differentiation and a centered numerical derivative was 1.23×10^{-5}. These checks establish reference backend agreement for the tested patches.

5 Unique data at matched exposure

Chinchilla compares text-training compute allocations, while recent data-constrained studies explicitly vary unique data and reuse [4, 5]. A PhaseWeave graph window allocates 144 spatial positions and yields 16 derived temporal positions. These counts track graph compute and provide no word-token equivalence. In a calibration on actual August windows, each arm trained the same 211,329-parameter width-64 model for 64 updates and 4,096 window presentations, with the same implementation and initial weights per seed. The nested window counts 256, 1,024 and 4,096 correspond to sixteen, four and one passes.

Fit seed	256 unique	1,024 unique	4,096 unique
20261125	0.245708	0.241932	0.241897
20261126	0.238083	0.237282	0.239582
20261127	0.240125	0.242018	0.241801

September validation subset MAE, log bps. Persistence is 0.242495 on the same 1,024 validation windows.

The lowest validation MAE occurs at a different unique training count for each of the three seeds. This calibration addresses reuse and does not identify a general compute-optimal scaling frontier. The registered GPU study crosses three widths with 65,536 and 131,072 unique windows, with selection among matched exposures. The expansion retains the original evaluation splits byte for byte. Scaling study and reproducible results.

6 Paired reference experiment

The frozen corpus has 294,912 FX windows. Each width-200 arm forecasts the one-second margins for both triangle orientations and receives identical quote histories, seven Gate trade slots and two document slots. The added reference inputs are three currency records, three BIS pair records and five overnight funding series. Both arms use the same 20-slot architecture and 2,150,866 trainable parameters. The control zeros the eleven reference vectors and masks them. Each arm normalizes its observed August inputs. Matched initialization, epoch permutations and learning-rate changes give both arms 16,384 updates across 16 full passes of 65,536 windows each. Validation selected epoch 15 with MAE 0.175562 for the control and epoch 16 with MAE 0.174222 for references. [9]

Holdout	Control	References	Paired change [95% interval]
September stress	0.159801	0.160031	$+0.000230$ $[-0.000170, +0.000730]$
October	0.156397	0.155883	-0.000515 $[-0.000862, -0.000185]$
Unseen CHF	0.177248	0.176691	-0.000557 $[-0.001459, +0.000540]$

One-second margin MAE in log bps. Change equals references minus control, computed before rounding.

The 2,500-draw paired bootstrap resamples UTC days. September stress and October contain 65,536 windows each over 12 and 26 days, respectively. Unseen CHF contains 32,768 windows over 26 days. October favors references under this shared initialization. Both other intervals span zero. The separately trained quote-only width-200 model has a slightly lower October MAE than either paired model. [9, 8]

Gate derivative and depth coverage. A separate UTC-aligned companion contains 1,104 applied funding settlements for four USDT perpetuals. All 294,912 FX anchors have all four rates when their settlement labels plus 60 seconds precede the anchor, subject to a 24-hour carry limit. Historical subscriber receipt times are unavailable. These derivative rates are distinct from the five overnight funding inputs in the paired training experiment. The only spot depth hour is 30 October, 12:00–13:00 UTC. It intersects 457 holdout anchors and zero training anchors. At the anchor, all three books meet a 250 ms age limit in 113 cases. Across all 16 frames the same limit admits zero windows. These companion data establish coverage and timing assumptions. [10]

References

[1] A. Schreiber, *GRH research atlas*, pinned source e941b50.
[2] D. Fenn et al., *The mirage of triangular arbitrage in the spot foreign exchange market*, arXiv:0812.0913.
[3] J. Kim et al., *Pure transformers are powerful graph learners*, arXiv:2207.02505.
[4] J. Hoffmann et al., *Training Compute-Optimal Large Language Models*, arXiv:2203.15556.
[5] N. Muennighoff et al., *Scaling Data-Constrained Language Models*, arXiv:2305.16264.
[6] G. Yang et al., *Tensor Programs V*, arXiv:2203.03466.
[7] A. Schreiber, *Historical torus subdivision*, oriented edge list and face word.
[8] PhaseWeave, *Width and circuit comparisons*, experiment results.
[9] PhaseWeave, *Paired reference forecast*, epoch history, matched arms and masks.
[10] PhaseWeave, *Gate derivative and spot-depth coverage*, frozen replay specification.